

Amendments to the Claims:

This listing of claims replaces all prior versions and listings of claims in the application:

Listing of Claims:

1. (Currently Amended) A grip for engaging a stent in a stent delivery catheter prior to delivery, the grip comprising a body region, ~~the body region having a first end and a second end and a hub region,~~ an outer diameter of the ~~first end~~ hub region being greater than an outer diameter of the ~~second end~~ body region,

~~wherein the outer diameter of the first end is greater than an outer diameter of the stent when the stent is in an unexpanded configuration, during use, the stent abuts the hub region.~~

2. (Currently Amended) The grip of claim 1 ~~further comprising a hub region,~~ wherein the hub region being is adjacent to the a first end of the body region, the outer diameter of the hub region having a diameter being greater than the an outer diameter of the first end of the body region.

3. (Currently Amended) The grip of claim 1 wherein the outer diameter of the body region is substantially tapered from the first end of the body region to the a second end of the body region.

4. (Original) The grip of claim 1 wherein at least a portion of the grip has a hardness of about 60 to about 90 as measured on the Shore A hardness scale.

5. (Original) The grip of claim 1 wherein at least a portion of the grip has a hardness of 70 to about 90 as measured on the Shore A hardness scale.

6. (Original) The grip of claim 1 wherein at least a portion of the grip is constructed from at least one material of the group consisting of: polyether ester, polyether block amides, PELLETHANE, TECOTHANE, polyurethane, rubber foam, silicon and any combination thereof.

7. (Original) The grip of claim 1 wherein at least a portion of the grip is radiopaque.

8. (Original) The grip of claim 1 wherein the grip is engaged to an inner shaft of a catheter assembly.

9. (Original) The grip of claim 8 wherein the grip defines at least a portion of a stent mounting region of the inner shaft.

10. (Currently Amended) The grip of claim 8 wherein ~~the catheter assembly comprises a stent, the stent having an unexpanded state and an expanded state, in the an~~ unexpanded state, at least a portion of the stent ~~being is~~ disposed about and engaged to at least a portion of the body region of the grip.

11. (Currently Amended) A stent delivery system comprising: a catheter, the catheter having an inner shaft and a retractable sheath, the inner shaft having at least one grip member engaged thereto, the at least one grip member comprising a body region; ~~the body region having a first end and a second end;~~ a hub region, an outer diameter of the first end hub region being greater than an outer diameter of the second end ~~so that the outer diameter is substantially tapered from the first end to the second end~~ body region; and a stent, the stent being expandable from an unexpanded state to an expanded state, in the unexpanded state, at least a portion of the stent being disposed about a portion of the inner shaft and engaged to at least a portion of the body region of the at least one grip, in the unexpanded state, the retractable sheath being

overlying the stent, ~~wherein the stent expands to the expanded state when the retractable sheath is retracted off of the stent, the stent is expanded to the expanded state,~~

~~wherein the outer diameter of the first end is greater than an outer diameter of the stent in its unexpanded state, during use, the stent abuts the hub region.~~

12. (Original) The stent delivery system of claim 11 wherein the stent comprises a plurality of struts.

13. (Original) The stent delivery system of claim 12 wherein the catheter exerts a longitudinal force upon individual struts of the stent when the sheath is retracted from about the stent, the at least one grip member reducing the longitudinal force the catheter exerts on the individual struts.

14. (Currently Amended) The stent delivery system of claim 11 wherein ~~the at least one grip member further comprises a hub region, the hub region being is adjacent to the a first end of the body region, the outer diameter of the hub region having a diameter being greater than the an outer diameter of the first end of the body region, in the unexpanded state an end of the stent being positioned adjacent to the hub region.~~

15. (Cancelled)

16. (Currently Amended) The stent delivery system of claim 11 wherein the at least one grip member comprises a first grip member and a second grip member, ~~the second an end of the body region of the first grip member being substantially adjacent to the second an end of the body region of the second grip member.~~

17. (Original) The stent delivery system of claim 16 wherein the stent comprises a first end portion, a second end portion and a body portion therebetween, in the unexpanded state

the first end portion of the stent being engaged to at least a portion of the body region of the first grip member, and the second end portion of the stent being engaged to at least a portion of the body region of the second grip member.

18. (Currently Amended) The stent delivery system of claim 17 wherein, in the unexpanded state, the body portion of the stent overlies the ~~second~~ end of the body region of the first grip member and the ~~second~~ end of the body region of the second grip member.

19. (Original) The stent delivery system of claim 12 wherein the at least a portion of the at least one grip member has a hardness of about 60 to about 90 as measured on the Shore A hardness scale.

20. (Original) The stent delivery system of claim 12 wherein the at least a portion of the at least one grip member has a hardness of about 70 to about 90 as measured on the Shore A hardness scale.

21. (Currently Amended) The stent delivery system of claim 11 wherein the at least a portion of the at least one grip member is constructed from at least one material of the group consisting of: polyether ester, polyether block amides, PELLETHANE, TECOTHANE, polyurethane, rubber foam, silicon and any combination there of.

22. (Original) The stent delivery system of claim 12 wherein the at least a portion of the at least one grip member is radiopaque.

23. (Currently Amended) A method, comprising:
providing a grip between the a catheter shaft and the an outer sheath; and
providing a stent between a portion of the grip and the outer sheath,

wherein the grip includes a body region; ~~the body region has a first end and a second end~~
~~and a hub region, an outer diameter of the first end is~~ hub region being greater than an outer
~~diameter of the second end~~ body region, and the outer diameter of the first end is greater than an
~~outer diameter of the stent in an unexpanded state~~ wherein, during use, the stent abuts the hub
region.

24. (Currently Amended) The method of claim 23 further comprising engaging at least a portion of the stent in an unexpanded state to at least a portion of the body region of the at least one grip.

25. (Previously Presented) The grip of claim 1, wherein the grip is at least partially constructed from a polymeric material.

26. (Previously Presented) The stent delivery system of claim 11, wherein the at least one grip member is at least partially constructed from a polymeric material.

27. (Previously Presented) The method of claim 23, wherein the grip is at least partially constructed from a polymeric material.

28. (New) The method of claim 1, wherein the outer diameter of the hub region is greater than an outer diameter of the stent when the stent is in an unexpanded state.

29. (New) The method of claim 11, wherein the outer diameter of the hub region is greater than an outer diameter of the stent when the stent is in its unexpanded state.

30. (New) The method of claim 23, wherein the outer diameter of the hub region is greater than an outer diameter of the stent when the stent is in an unexpanded state.

31. (New) The stent delivery system of claim 11, wherein the outer diameter of the body region is substantially tapered from a first end of the body region to a second end of the body region.

32. (New) The method of claim 23, wherein the outer diameter of the body region is substantially tapered from a first end of the body region to a second end of the body region.